CONN SIZE	FILTER DESIGNATION	FILTER CIRCUITS	CAPACITANCE		3 dB MAX CUTOFF FREQ (MHz)	DIELECTRIC WITHSTANDING VOLTAGE	CONTACT RATING	CONTACT RESIST	WORKING VOLTAGE DC	MINIMUM INSERTION LOSS-DECIBELS (dB)			
			VALUE	TOLERANCE					-25°C TO +125°C	20 MHz	100 MHz	500 MHz	1 GHz
25	012	FT	840pF	+30% -30%	6	300 V	5 AMPS	.010 OHM MAX	100 VDC	5	18	31	37

MARKING



NOTES:

1. SHELL: STEEL, TIN PLATE
2. INSULATORS: UL94V-0
3. CONTACTS: COPPER ALLOY: .000030 GOLD IN SOCKET CONTACT MATING AREAS





THIS DOCUMENT CONTAINS PROPRIETARY INFORMATIONAND IS COPYRIGHTED. EXCEPT WITH THE WRITTEN PERMISSION OF SPECTRUM CONTROL INC., OR ITS SUBSIDIARIES, SUCH INFORMATION SHALL NOT BE PUBLISHED OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE AND THIS DOCUMENT SHALL NOT BE DUPLICATED IN WHOLE OR IN PART.

REV. NO.	CHANGE NOTICE
5	CN 199114

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES.

CADD SCALE: FULL
PLOT SCALE: 2x

TOLERANCES UNLESS OTHERWISE SPECIFIED
Fractions ± 1/64
Dec. .xx±
Dec. .xxx± .015
Angles ±0° 30'

CODE IDENT. NO. 33095

SPECTRUM CONTROL INC.
CONNECTOR PRODUCTS DIVISION
ERIE, PENNSYLVANIA

Dwn. KRDZALIC
Date 12/11/00
Apvd. K WOOD
Sheet 1 of 1

Description 25 POSITION LOW PROFILE,SOCKET/PCB TAIL FILTERED CONNECTOR

B 56-523-012

Quality Products From The Specialists In Electro-Magnetic Compatibility