	I G	н <b>г</b>	m	D		C	D	A		
4	R 22.6 Max () () () () () () () () () () () () ()	V Thread	S			<image/>	OUT SHOWN AS EXAMPLE			4
N	-Standard : Based on MIL-DTL-38999 Series III         -Shell Material       : Aluminium         -Shell Plating       : Black Zinc Nickel         -Insulator       : Thermoplastic         -Contacts       : Copper Alloy         -Seals & Grommet       : Silicon Elastomer         -Contact Plating       : Gold over copper Alloy 0.8µm r         -Durability       : 500 Mating cycles         -Delivered with Souriau contacts and Accessories         -Temperature Range       : -65°C to +175°C	Keying Shown as	Connector dimension           Dim         Nominal           A         38.1±0.3           B         23.82+0.1/-0.15           R         32.5Max           S         34.9±0.4           W         2.2+0.9/-0.1           VV THREAD         M18x1-6g			due to a use o the Specifications i (profession P	ot be liable for any non-confor f the Products which does not ssued by either of the Parties nal recommendation, technica Country Jun FR N: 8D713Z26BB	comply with or by a third party		2
	-Salt Spray : 500 hours				A 29-09-2016	First Release	) - hy		MOD N°	_
	-Mass : 30.54 g ± 10%				esigned By:	Date:	Aluminium Recepta	CUSTOMER DRAWING		
	BASIC SERIES:8D7SHELL TYPE : Jam nut ReceptacleCONTACT TYPE : Standard Crimp ContactSHELL SIZE : 13PLATING : Z = Black Zinc Nickel	13 Z 26 B B	ORIENTA CONTACT TYPE : SOCKET(500 I CONTACT LAYOU	Matings)	SCALE NA SOURIAU FORMAT		General linear Tolerances: ± SOURIAU.COM SOURIAU DRG N	NPRDS / PROJECT 859 This document is the pro SOURIAU it must not be reprodu communicated without p	iced or	1
	H G			D	A3	С	8D713Z26BB-C		1/2	
		I I		U	I	0	I D	I A		

ſ	I	D	П	m	D	O	Φ	A		
	Со	ntact Layout				Panel cutout				
	26			JAM NUT RECEPTACLE (TYPE 7)						
4										
		2#12 6#22D								
_	13-26						<u> </u>			
	Ctc	X Y	_			< ØC >				
	Α	0 3.47								
	В	2.47 4.34			Г	Dim Nominal	_			
	С	2.47 -4.34	_			B 24.26+0/-0.25				
ယ	D E	0 -3.47 -2.47 -4.34	_			ØC 25.65+0.25/-0	0		3	
	F	-2.47 -4.34	_							
	1	3.25 0	_							
	2	-3.25 0								
2						the Specifications issued by ei (professional recomm	mendation, technical notice. Country Jurisdiction	nird party	2	
					A 29-09-2016	First Release				
					ISS DATE Designed By:	Latest modification - by Date:	CU	MOI	D N°	
			TITLE     Aluminium Receptacle 8D series				) series			
_					SCALE -	General I Toleran ±	ices:	IPRDS / PROJECT <b>859</b>		
					SOURIAU		AU.COM	This document is the property of SOURIAU it must not be reproduced or communicated without permission		
					FORMAT	SOUR	IAU DRG N°	SHI	ET	
					A3	8D7:	13Z26BB-C	2,	/2	
	H	G	l F	E	D	C	В	A		