1	۳ ۳	m		0	₿		]
4	Z						4
ω				LAYOUT SHOWN AS EX	AMPLE		3
	Keying Show	vn as example					
	CHARACTERISTICS	Connector dimension					
	-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal					
	Shell Material   Aluminium   ØS   29.4 Max     Z   31 Max     Shell Plating   : Olive drab Cadmium   VV THREAD   M18x1-6g     Insulator   : Thermoplastic   VV THREAD   M18x1-6g     Contacts   : Copper Alloy   : Silicon Elastomer   : Silicon Elastomer						
N	-Contact Plating : Gold over copper Alloy 0.8µm minimum			FR	Not Listed		2
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories		PN: 8D513W08BA				
	-Temperature Range65°C to +175°C			<b>5</b>			-
	-Salt Spray : 500 hours		A 19-10-2016	FIRST Release			
	-Mass : 26.6 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	+
	TITLE Aluminium Plug 8D serie						
<u> </u>	BASIC SERIES: 8D 5 - 13 W 08 B A   SHELL TYPE : Plug with RFI Shielding - - 13 W 08 B A		SCALE -{	General linear Tolerances:	NPRDS / PROJECT <b>859</b>		-
	CONTACT TYPE : Standard Crimp Contact ORIENTATION : A			SOURIAU WWW.SOURIAU.COM This document is the pro- SOURIAU it must not be reprodu			
	SHELL SIZE : 13 CONTACT TYPE : SOCKET(500		communicated without permiss				
	PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 13-08	FORMAT	SOURIAU	DRG N°	SHEET	
		<u> </u>	A3	8D513W0	08BA-C	1/2	
·	H G F	E	D	С	ВА		-

r	Ŧ	۵	г п	m		0
		Contact Layout				
4		$X \begin{pmatrix} G \\ F \\$				
		Contacts       (insert arrangement 13-8)       Intact billon     Contact location       X-axis D     Y-axis (mm)     (mm)       A     +.065 (1.65)     +.157 (3.99)       B     +.170 (4.32)     +.000 (0.00)       C     +.120 (3.05)    120 (3.05)       D    000 (0.00)    170 (4.32)       E    120 (3.05)    120 (3.05)       F    170 (4.32)     +.000 (0.00)       G    065 (1.65)     +.157 (3.99)       H     +.000 (0.00)     +.044 (1.12)				
۵	Shell Arrangement Nu size no. c 13 -8	imber of Size Service Contact Supersede ontacts contacts rating location 8 20 I All MS20051-				
	-					SOURIAU shall not be liable for an due to a use of the Products wi the Specifications issued by either o (professional recommenda
N						Count FR PN: 8D513\
					A 19-10-20 ISS DATE Designed By:	116 First Release
					SCALE	Alumir General linear
<u> </u>					NA	Tolerances:
					SOURIA	
					FORMAT A3	SOURIAU 8D513W
	Н	G	F F	E \	D	C

