	יד ס	m			0	₩ 2	>
	peault VV						
					LAYOUT SHOWN AS EX	AMPLE	
	Key	ing Shown as example					
CHARACTERISTICS		Connector di	mension				
Standard : Based on MIL-DTL-38999 Series III		Dim	Nominal				
-Shell Material : Aluminium		ØS Z	25 Max 31 Max		SOURIAU shall not be liable for any	non-conformity or damage	
-Shell Plating : Black Zinc Nickel VV THREAD M15x1-6g				due to a use of the Products which does not comply with			
-Insulator : Thermoplastic				the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Contacts : Copper Alloy						. ,	
-Seals & Grommet : Silicon Elastomer					Country	Jurisdiction & Control List	
-Contact Plating : Gold over copper Al	oy 0.8µm minimum			FR Not Listed			
	: 500 Mating cycles PN: 8D511Z02AC						
-Delivered with Souriau contacts and Accesso	IES						
-Temperature Range : -65°C to +175°C				A 18-10-2016	First Release		
-Salt Spray : 500 hours							
-Mass : 14.61 g ± 10%				ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°
				TITLE		um Plug 8D series	-
BASIC SERIES: 8D 5	5 - 11 Z 02 A	С		SCALE	General linear Tolerances:	NPRDS / PROJECT	
SHELL TYPE : Plug with RFI Shielding				NA 1		859	
CONTACT TYPE : Standard Crimp Contact			ORIENTATION : C			This document is the SOURIAU	
				SOURIAU	SOURIAU WWW.SOURIAU.COM it must not be reproduced or communicated without permissi		
SHELL SIZE : 11 CONTACT TYPE : PIN(500 Matings)				FORMAT	COUDIALL		
			CONTACT LAYOUT : 11-02		SOURIAU		SHEET
PLATING : Z = Black Zinc Nickel				A3	8D511Z0		1/2

r		G	н г	m		0
		Contact Layout				
4	.x. (2)	+Y IB IA IB IA -Y .095 .41mm) .095				
	Continue of the second	tion X-axis Y-axis (mm) (mm) +.095 (2.41) +.000 (.00)				
ω						
	-				[
						SOURIAU shall not be liable for a due to a use of the Products w the Specifications issued by either (professional recommenda
N						Count FR
						PN: 8D511
						116 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumi
_					SCALE NA	General linear Tolerances: ±
					SOURIA	U WWW.SOURIAU.
					FORMAT	SOURIAL
l		<u> </u>	F	r i	A3	8D511Z
	Н	G		E	D	C

