ד ים ישר ד						
A Z	4					
	LAYOUT SHOWN AS EXAMPLE 3					
Keying Shown as example						
CHARACTERISTICS Connector dimensi						
-Standard : Based on MIL-DTL-38999 Series III Dim No.						
Shell Material       Aluminium       DS       25 Mdx         Shell Material       Aluminium       Z       31 Max         Shell Plating       Black Zinc Nickel       VV THREAD       M15x1-6g         Insulator       Thermoplastic       VV THREAD       M15x1-6g         Contacts       Copper Alloy       Copper Alloy       Copper Alloy						
-Seals & Grommet : Silicon Elastomer	Country     Jurisdiction & Control List       FR     Not Listed					
-Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : 500 Mating cycles	-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles					
-Delivered with Souriau contacts and Accessories	PN: 8D511Z02SA					
-Temperature Range - 65°C to +175°C	A 18-10-2016 First Release					
-Salt Spray : 500 hours						
	ISS         DATE         Latest modification - by         MOD N°           Designed By:         Date:         CUSTOMER DRAWING					
TITLE Aluminium Plug 8D series						
→ BASIC SERIES: 8D 5 - 11 Z 02 S A SHELL TYPE : Plug with RFI Shielding	SCALE General linear NPRDS / PROJECT NA ± 859					
CONTACT TYPE : Standard Crimp Contact	ORIENTATION : A SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or					
SHELL SIZE : 11 CONTACT TYPE :	CKET(500 Matings)					
PLATING : Z = Black Zinc Nickel CON	CT LAYOUT : 11-02 FORMAT SOURIAU DRG N° SHEET					
	A3 8D511Z02SA-C 1/2					
H G F E	D C B A					

r	Ŧ	۵	וד	m	U	0
		Contact Layout				
4	. X- .0: (2-	+Y IB IA +Y +X 95 4(mm) (2.4(mm))				
	Cont positi ID A A B Shell Arrangement size no. 11 -2	X-axis         Y-axis           (mm)         (mm)           +.095 (2.41)         +.000 (.00)          095 (2.41)         +.000 (.00)				
ယ						
	L					
						SOURIAU shall not be liable for a due to a use of the Products the Specifications issued by either (professional recommend
N						Cour
						PN: 8D51
					A 18-10-20 ISS DATE	16 First Release Latest modification - by
					Designed By:	Date:
					TITLE	Alum
<u> </u>					SCALE NA	General linear Tolerances:
					SOURIA	U WWW.SOURIAU.
					FORMAT A3	SOURIA 8D511
L	Н	G	F	E	D	C C

