	۲ G	П	m	D	0	Ð	Þ	
4	Z	ØF						4
					LAYOUT SHOWN AS EX	AMPLE		
		Keying Shown as e	example					
	CHARACTERISTICSStandard : Based on MIL-DTL-38999 Series III		Connector dimension Dim Nominal					
	-Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy		F19.05 MaxZ31.5 MaxVV THREADM15x1-6g		SOURIAU shall not be liable for any due to a use of the Products wh the Specifications issued by either of (professional recommendati	ch does not comply wi the Parties or by a thir	ith	
\sim	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum				Country FR	Jurisdiction & Not L		2
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories				PN: 8D1117	98SN		
	-Temperature Range _: -65°C to +175°C -Salt Spray : 500 hours			A 27-09-20	016 First Release			
				ISS DATE Designed By:	Latest modification - by Date:	CUST	MOD N°	,
				TITLE	Aluminium	Inline plug 8D	series	
	BASIC SERIES: 8D 1 - 11 Z	98 S N		SCALE	General linear Tolerances:	NP	RDS / PROJECT	
<u> </u>	SHELL TYPE : In line Receptacle CONTACT TYPE : Standard Crimp Contact		SOURIAU This document is SOURIAU SOU it must not be					
	SHELL SIZE : 11 PLATING : Z = Black Zinc Nickel		CONTACT TYPE : SOCKET(500 Matings) CONTACT LAYOUT : 11-98	-	SOURIAU		mmunicated without permission SHEET	
				A3	8D111Z9	8SN-C	1/2	
	H G I	F	E	D	C I	В	I A	

ſ	т	Q	нт –	m	D	0	σ	A	
4	- <u>x</u>	$ \bigoplus_{i=1}^{A} \bigoplus_{i=1}^{A} \bigoplus_{j=1}^{B} \bigoplus_{i=1}^{B} \bigoplus_{i=1}^{A} \bigoplus_{i=1}^{B} \bigoplus_{j=1}^{B} \bigoplus_{i=1}^{A} \bigoplus_{i=1}^{A} \bigoplus_{j=1}^{A} \bigoplus_{j=1}^{A} \bigoplus_{i=1}^{A} \bigoplus_{j=1}^{A} \bigoplus_{j=1}^{A} \bigoplus_{j=1}^{A} \bigoplus_{i=1}^{A} \bigoplus_{j=1}^{A} \bigoplus_{j=1}^{A} \bigoplus_{i=1}^{A} \bigoplus_{j=1}^{A} \bigoplus_{i=1}^{A} \bigoplus_{j=1}^{A} \bigoplus_{$							4
	Contact position ID A B C C D E	Contacts X-axis (mm) (mm) +.130 (3.30) +.130 (3.30) +.130 (3.30) +.000 (0.00) +.130 (3.30) +.000 (0.00) +.065 (1.65) 113 (2.87) 065 (1.65) 113 (2.87) 130 (3.30) +.000 (0.00) *.000 (0.00) to 000 (0.00)							
ω									3
						SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
N		Country Jurisdiction & Control List FR Not Listed PN: 8D111Z98SN A 27-09-2016 First Release							2
					ISS DATE Designed By: TITLE		ninium Inline plug 8D		
_ _					SCALE NA SOURIAU		AU.COM	IPRDS / PROJECT 859 This document is the property of SOURIAU it must not be reproduced or communicated without permission	1
	H	G	F	E	FORMAT A3 D		RIAU DRG N° 11Z98SN-C B	A SHEET	