

UM-DELTA V/A/T/SI/BFI


Order No.: 5603254



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=5603254>

VARIOFACE interface module with knife disconnection, fuse and fuse failure display

Commercial data

| | |
|----------------|---|
| GTIN (EAN) |  4 017918 923075 |
| Note | Made-to-order |
| sales group | I630 |
| Pack | 1 pcs. |
| Customs tariff | 85369010 |

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

| | |
|---|--|
| Nominal voltage U_N | 24 V DC |
| Max. current carrying capacity per branch | 50 mA (in as-supplied state, with one 50 mAF fuse, max. 1 A permitted) |
| Number of positions | 16 |
| Width | 61 mm |
| Height | 126 mm |
| Depth | 71 mm |
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

| | |
|-----------------------|-------------------------|
| Mounting position | Any |
| Standards/regulations | IEC 60664 |
| | IEC 60664 A |
| | DIN VDE 0110 |
| | DIN VDE 0160 (in parts) |

Connection data

| | |
|--|------------------------------|
| Connection 1 | PCB connection |
| Type of connection | Screw connection |
| Conductor cross section solid min. | 0.2 mm ² |
| Conductor cross section solid max. | 4 mm ² |
| Conductor cross section stranded min. | 0.2 mm ² |
| Conductor cross section stranded max. | 2.5 mm ² |
| Conductor cross section AWG/kcmil min. | 24 |
| Conductor cross section AWG/kcmil max | 12 |
| Stripping length | 7 mm |
| Connection 2 | Flat-ribbon cable connection |
| Type of connection | Pluggable |

Certificates / Approvals



Certification

CUL, UL

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;