

Contact insert - RC-17P1N220000 - 1607009

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Contact insert, Number of positions: 17, Type of contact: Male connector, Solder-in connection

The figure shows the 6-pos. product version



Key commercial data

| | |
|--------------------------------------|----------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 24.1 GRM |
| Custom tariff number | 85366990 |
| Country of origin | Germany |

Technical data

General

| | |
|--|----------------------|
| Insertion/withdrawal cycles mechanical | 50 |
| Direction of rotation of contact chamber numbering | Standard |
| Coding | N |
| Contact connection method | Solder-in connection |
| Type of contacts | Male connector |
| Number of positions | 17 |
| Contact diameter of power contacts | 1 mm |
| Nominal current per power contact at 25°C | 8 A |

Material

| | |
|--------------------|-----------------------------|
| Insulator material | PBT |
| Contact material | CuZn |
| Contact surface | Nickel-plated, gold coating |

Specifications according to DIN EN 61984:2001

| | |
|---|-------|
| Nominal / operating voltage of power contacts | 150 V |
|---|-------|

Contact insert - RC-17P1N220000 - 1607009

Technical data

Specifications according to DIN EN 61984:2001

| | |
|---|--------|
| Rated surge voltage of power contacts | 1.5 kV |
| Surge voltage category of power contacts | II |
| Pollution degree of power contacts | 3 |
| Surge voltage category of signal contacts | II |
| Pollution degree of signal contacts | 3 |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260708 |
| eCl@ss 7.0 | 27440312 |
| eCl@ss 8.0 | 27440312 |

ETIM


| | |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC001121 |
| ETIM 5.0 | EC002641 |

UNSPSC


| | |
|---------------|----------|
| UNSPSC 6.01 | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11 | 43172015 |
| UNSPSC 12.01 | 43201404 |
| UNSPSC 13.2 | 43201404 |

Drawings

Schematic diagram




Schematic diagram



Contact insert - RC-17P1N220000 - 1607009

Drilling diagram



Schematic diagram

