ت ال	т п		0	₿ >	
A Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z					
			LAYOUT SHOWN AS EXAM	MPLE	
	Keying Shown as example				
CHARACTERISTICS	Connector dimension	1			
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal ØS 25 Max	-			
-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	Z 31 Max VV THREAD M15x1-6g		SOURIAU shall not be liable for any no due to a use of the Products which the Specifications issued by either of th (professional recommendation	does not comply with e Parties or by a third party	
-Seals & Grommet : Silicon Elastomer ► Contact Plating : Gold over copper Alloy 0.8µm minimum			Country FR	Jurisdiction & Control List Not Listed]
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D511F0	4PD	
-Temperature Range -65°C to +200°C		A 15-10-2016	First Release		
-Salt Spray : 48 hours 		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°
		TITLE	TITLE Aluminium Plug 8D series		
→ BASIC SERIES: 8D 5 - 11 F 04 → SHELL TYPE : Plug with RFI Shielding	L P D	SCALE -	General linear Tolerances:	NPRDS / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	ORIEN CONTACT TYPE : PIN(5)			M This document is the pro SOURIAU it must not be reproduc communicated without pe	ced or
PLATING : F = Nickel	CONTACT LAY	OUT : 11-04 FORMAT	SOURIAU D	DRG N°	SHEET
		A3	8D511F04	IPD-C	1/2

ſ	Ŧ	G	г П	m		0		
		Contact Layout						
4	-X	$ \begin{array}{c} $						
	Shell Arrangement Numb	X-axis Y-axis (mm) +0.65 (1.65) -0.65 (1.65) -0.65 (1.65) -0.65 (1.65) -0.65 (1.65) -0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) -0.65 (1.65) -0.65 (1.65) -0.65 (1.65) -0.65 (1.65) -0.65 (1.65) -0.65 (1.65) -0.65 (1.65) <th>]</th> <th></th> <th></th> <th></th> <th></th>]					
ω	11 -4 4	20 I All MS20050-4						
	+					SOURIAU shall not be liab due to a use of the Pro the Specifications issued by (professional recor	oducts w y either o	
N						PN: 80	Count FR D511	
					A 15-10-20 ISS DATE Designed By:	016 First Release Latest modification - by Date:		
					TITLE SCALE NA	Genera 	Alumin al linear rances: ±	
					SOURIA	OURIAU WWW.SOURIAU.		
					FORMAT A3	SOU 8D	RIAU 511F	
L	Н	G	F	E	D	С		

