工	G	нт. П	т	C C







Keying Shown as example

CHARACTERISTICS

ယ

 \sim

-Mass

BASIC SERIES:

SHELL SIZE : 13

Н

SHELL TYPE : Square Flange Receptacle

CONTACT TYPE : Standard Crimp Contact

PLATING : W = Olive drab Cadmium

-Standard : Based on MIL-DTL-38999 Series III

-Shell Material	: Aluminium		
-Shell Plating	: Olive drab Cadmium		
-Insulator	: Thermoplastic		
-Contacts	: Copper Alloy		
-Seals & Grommet	: Silicon Elastomer		
-Contact Plating	: Gold over copper Alloy $0.8 \mu m$ minimum		
-Durability	: 500 Mating cycles		
-Delivered with Souriau contacts and Accessories			
-Temperature Range	65℃ to +175℃		
-Salt Spray	: 500 hours		

: 20.37 g ± 10%

8D 0

G

13

W


98

S

F

В

Connector dimension			
Dim	Nominal		
Р	3.25±0.2		
РР	4.93±0.2		
R1	23.01		
R2	20.62		
S	28.6±0.3		
V	20.83+0/-1.25		
W	2.1/2.5		
Z	31.5 Max		
VV THREAD	M18x1-6g		



0		Φ		Þ		
			5			4
LAY	YOUT SHOWN AS EXA	MPLE				3
SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed PN: 8D013W98SB						2
First Release					MOD N°	
Date:			CUSTO	MER DRAWING		
Aluminium Receptacle 8D series						
$\exists \bigoplus$	General linear Tolerances: ±		NPR	DS / PROJECT 859		1
WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						
	SOURIAU I 8D013W9				SHEET	
С		B		A	-	J

		۵	ار (m		0	
		Contact Layout					Panel Cutout
4	د.	$x_{1}^{(A)} \bigoplus_{\substack{H \in \mathcal{H} \\ F \in \mathcal{H} \\ F \in \mathcal{H} \\ Y \\ Y}} \bigoplus_{\substack{K \in \mathcal{H} \\ F \in \mathcal{H} \\ Y \\ Y}} \bigoplus_{\substack{K \in \mathcal{H} \\ F \in \mathcal{H} \\ Y \\ $				SQUARE FLANGE RECEPTACLE (REAR MOUNTING R1	TYPE 0)
	Contro position A B C C D C C D F F G G H J J K	In ID (mm) (mm) +.000 (0.00) +.195 (4.95) +.125 (3.18) +.150 (3.81) +.193 (4.90) +.030 (0.76) +.104 (4.17) 105 (2.67) +.000 (0.00) 135 (3.43) 164 (4.17) 105 (2.67) 193 (4.90) +.030 (0.76) 125 (3.18) +.150 (3.81) +.056 (1.65) 015 (0.38)					
ω	Shell Arrangement N size no. cc	-Ubb (1.06) -U15 (U.38) lumber Size Service Contact Supersedes of contacts rating location Supersedes 10 20 I All MS20051-98					Dim ØA ØAA R1 ØT
						due to a use the Specifications	not be liable for any of the Products whi issued by either of onal recommendati
N							Country FR
						Р	N: 8D013W
					A 16-10-201 ISS DATE Designed By:	.6 First Release Latest modificatio Date:	n - by
					TITLE		Aluminium
<u> </u>					SCALE NA		General linear Tolerances: ±
					SOURIAL	J www.	SOURIAU.C
					FORMAT A3		SOURIAU 8D013W9
	Н	G	F	E	D	С	

