
Spec Sheet

SMD Power Inductors (NR series)

NR4010T220M



Features

- Item Summary
 22uH±20%, 0.36A, 4.0x4.0x1.0mm
- Lifecycle Stage
 Mass Production
- Standard packaging quantity (minimum)
 Taping Embossed 5000pcs


Products characteristics table

Inductance	22 uH ± 20 %
Case Size (mm)	4.0x4.0
Rated Current (max)	0.36 A
Saturation Current (max)	0.36 A
Temperature Rise Current (max)	0.4 A
DC Resistance (max)	1.044 Ω
DC Resistance (typ)	0.87 Ω
LQ Measuring Frequency	100 kHz
Self Resonant Frequency (min)	19 MHz
Operating Temp. Range	-25 to +120 ℃ (Including-self-generated heat)
Temperature characteristic (Inductance change)	± 20 %
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (173 subst.)	Yes
Halogen Free	Yes
Soldering	Reflow

External Dimensions

Dimension L	4.0 ±0.2 mm
Dimension W	4.0 ±0.2 mm
Dimension H	Max 1.0 mm
Dimension e	1.1 ±0.2 mm
Dimension f	2.5 ±0.2 mm

Recommended Land Patterns



2017.04.30

SMD Power Inductors (NR series)

NR4010T220M



Dimension unit: mm unit: inch

Length: 4.0 +/- 0.2 (0.157 +/- 0.008)

Width: 4.0 +/- 0.2 (0.157 +/- 0.008)

Height: 1.0 max. (0.039 max.)

Inductance: 22 uH (test freq at 0.1MHz)
DC Resistance: 0.87 / 1.044 ohm (typ/max)

Saturation Current: 360 mA (max) Temp. rise Current: 400 mA (max)

Saturation current typical: 30% reduction from initial L value.

Temp rise Current typical: Temperature will rise by 40 deg C

