т Q Т	m		0	₿ >	
			LAYOUT SHOWN AS EXAMP	PLE	
Keying Sh	nown as example				
CHARACTERISTICS	Connector dimension				
	Dim Nominal ØS 25 Max				_
-Shell Material : Aluminium -Shell Plating : Black Zinc Nickel	Z 31 Max		SOURIAU shall not be liable for any non due to a use of the Products which d		
-Insulator : Thermoplastic	VV THREAD M15x1-6g		the Specifications issued by either of the	Parties or by a third party	
-Contacts : Copper Alloy			(professional recommendation, t	echnical notice.)	
-Seals & Grommet : Silicon Elastomer			Country	Jurisdiction & Control List	
-Contact Plating : Gold over copper Alloy 0.8µm minimum			FR	Not Listed	
-Durability : 500 Mating cycles			PN: 8D511Z05	PN	
-Delivered with Souriau contacts and Accessories					
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 18-10-2016 Fi	rst Release		
-Mass : 14.83 g ± 10%		ISS DATE	Latest modification - by		MOD N°
		Designed By:	Date:	CUSTOMER DRAWING	
		TITLE	TITLE Aluminium Plug 8D series		
BASIC SERIES: 8D 5 - 11 Z 05 P N	N	SCALE	General linear	NPRDS / PROJECT	
	`	NA -		859	
SHELL TYPE : Plug with RFI Shielding	L			This document is the proper	rty of
CONTACT TYPE : Standard Crimp Contact	ORIENTATION : N	SOURIAU	WWW.SOURIAU.COM	it must not be reproduced	
SHELL SIZE : 11 CONTACT TYPE : PIN(500 Matings)				communicated without perm	nission
PLATING : Z = Black Zinc Nickel	CONTACT LAYOUT : 11-05	FORMAT A3	SOURIAU DF		SHEET
			8D511Z05F		1/2

r	工	G	וד	m	D	0	
		Contact Layout					
4	-×_	$ \begin{array}{c} & & \\ & & \\ & \\ & \\ & \\ & \\ & \\ & \\ & $					
		+.065 (1.65) +.056 (1.42) +.113 (2.87)055 (1.65) +.000 (0.00)130 (3.30) 113 (2.87)065 (1.65) 065 (1.65) +.056 (1.42) ber of Size Service Contact Supersedes tacts contacts rating location					
ω	11 -5 5	5 20 I All MS20050-5	1				
	-					SOURIAU shall not be liable due to a use of the Produ the Specifications issued by ei (professional recomm	ucts w ither c
N						PN: 8D5	Count FR 511
					A 18-10-20 ISS DATE Designed By:	016 First Release Latest modification - by Date:	
_					TITLE SCALE NA	Alu General li Tolerand ±	ces:
					SOURIA		
					FORMAT A3	SOUR 8D51	
L	Н	G	F	E	D	C	

