	т Q Т	m		0	σ		
LANDUT SHOWN AS EXAMPLE Connector dimension Standard: Island on ML-CTI-SIB99 Series III Connector dimension Shell Plating Riack Zinc Nockel -insulator Standard: Standard: Standard Compe Alloy O.Bum minimum Shell Plating Silce Cooper Alloy -insulator Scole Riack Zinc Nockel -insulator Scole Riack Zinc Nockel -insulator Silce Cooper Alloy -seals & Grommet Silce Cooper Alloy O.Bum minimum <	4						4
CHARACTERISTICS Standard: Based on MIL-011-38999 Series III Standard: Based on MIL-011-38999 Series III Standard: Based on MIL-011-38999 Series III Standard: Standard: Ching Standard: Based on MIL-011-38999 Series III Standard: Sta				LAYOUT SHOWN AS	EXAMPLE		3
Standard : Based on MIL-DTL-38999 Series III Data	Keying Shown a	s example					
Shell Material : Aluminium Shell Material : Aluminium Shell Material : Black Zinc Nickel - Insulator : Thermoplastic - Contact Plaing : Gold over copper Alloy 0.8µm minimum - Outability : Sold over copper Alloy 0.8µm minimum - Outability : Sold over copper Alloy 0.8µm minimum - Outability : Sold over copper Alloy 0.8µm minimum - Outability : Sold over copper Alloy 0.8µm minimum - Outability : Sold over copper Alloy 0.8µm minimum - Outability : Sold over copper Alloy 0.8µm minimum - Outability : Sold over copper Alloy 0.8µm minimum - Outability : Sold over copper Alloy 0.8µm minimum - Outability : Sold over copper Alloy 0.8µm minimum - Outability : Sold over copper Alloy 0.8µm minimum - Outability : Sold over copper Alloy 0.8µm minimum - Outability : Sold copper Alloy 0.8µm minimum - Outa							
-Delivered with Souriau contacts and Accessories -Temperature Range :-65°C to +175°C -salt Spray : 500 hours BASIC SERIES: 8D SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE 13 PLATING : Z Basic Series 03 SHELL SIZE : CONTACT TYPE SHELL SIZE : Souriact PLATING : Z Basic Stick Since	-Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer	ØS 29.4 Max Z 31 Max		due to a use of the Products w the Specifications issued by either (professional recommend	which does not comply v of the Parties or by a th ation, technical notice.) try Jurisdiction	vith ird party & Control List	2
-Salt Spray : 500 hours -Salt Spray : 500 hours A 19-10-2016 First Release ISS DATE Latest modification - by Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Plug 8D series TITLE Aluminium Plug 8D series SCALE			PN: 8D513Z03SA				
BASIC SERIES: 8D 5 13 Z 03 S A BASIC SERIES: 8D 5 - 13 Z 03 S A CONTACT TYPE Stell TYPE			A 19-10-2016	First Release			
BASIC SERIES: 8D 5 - 13 Z 03 S A State SCALE NPRDS / PROJECT 859 SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact ORIENTATION : A NA SCALE NA State					CUS) N°
BASIC SERIES: SD SD <td></td> <td></td> <td>TITLE</td> <td colspan="3">Aluminium Plug 8D series</td> <td></td>			TITLE	Aluminium Plug 8D series			
CONTACT TYPE : Standard Crimp Contact ORIENTATION : A SHELL SIZE : 13 CONTACT TYPE : SOCKET(500 Matings) PLATING : Z = Black Zinc Nickel CONTACT Nickel				Tolerances:	N		1
PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 13-03			SOURIAU WWW.SOURIAU.COM SOURIAU it must not be reproduced or				
				SOURIAL			
			A3			1/2	2

-	I	ര	וד	m	D		0	
		Contact Layout						
4		03						
_		3#16 13-03						
	Ctc A B C	X Y 2.39 1.47 0 -2.79 -2.39 1.47						
ယ								
						d	RIAU shall not be lia ue to a use of the Pr ecifications issued b (professional recc	oducts v y either
N								Coun FR
							PN: 8	D513
						10-2016 First Rele	ease modification - by	
					Designed By:		Date:	
					ТІТІ	.E		Alumi
					SCALE NA		Tole	ral linear erances: ±
					SOUR	IAU	WWW.SOUF	RIAU.
				_	FORMAT A3		SOL 8D	JRIAU 5132

G

Н

F

Е

D

С

