	т	۵	ال (т			0	Φ		
4			ØS							4
ယ							LAYOUT SHOW	/N AS EXAMPLE		3
			Keying Sho	wn as example						
	CHARACTERISTICS			Connector dimension	_					
	-Standard : Based on MIL-DT	L-38999 Series III		Dim Nominal	_					
	-Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer				SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)					
\sim	-Contact Plating : Go	ld over copper Alloy 0.8µm minir	num			CountryJurisdiction & Control ListFRNot Listed			2	
		-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories				PN: 8D513W98BB				
		5°C to +175°C				A 19-10-201	6 First Release			
		0 hours $7 + 10\%$				ISS DATE	Latest modification - by		MOD) N°
	-Mass : 25	.7 g ± 10%				Designed By:	Date:	CL	JSTOMER DRAWING	
					TITLE	E Aluminium Plug 8D series				
	BASIC SERIES: SHELL TYPE : Plug with RFI S	8D 5 - 13 Shielding	W 98 B B			SCALE NA	General Tolerar ±	nces:	NPRDS / PROJECT 859	
	CONTACT TYPE : Standard Crimp Contact ORI			IENTATION : B	SOURIAU WWW.SOURIAU.COM SOURIAU it must not be reproduce			it must not be reproduced or		
	SHELL SIZE : 13					500000			communicated without permission	
	PLATING : W = Olive	drab Cadmium		CONTACT L	AYOUT : 13-98	FORMAT A3		RIAU DRG N°	SHE	
l		1	1					L3W98BB-C	1/2	2
	Н	G	l F	E N	J/	D	C	В	A	

_	I	۵	וד	m	D	0
		Contact Layout				
4		$x_{1} \begin{pmatrix} \bullet & \bullet \\ \bullet & $				
	Conti position A B B C C D D E G G G H H J J K	n ID (mm) (mm) + 000 (0.00) + .195 (4.95) + .125 (3.18) + .150 (3.81) + .123 (4.90) + .030 (0.76) + .104 (4.17) 105 (2.67) + .000 (0.00) 135 (3.43) 164 (4.17) 105 (2.67) 193 (4.90) + .030 (0.76) 193 (4.90) + .030 (0.76) 193 (4.90) + .030 (0.76) + .000 (0.50) 135 (3.43) 193 (4.90) + .030 (0.76) + .045 (1.85) 015 (0.38)				
ى س	Shell Arrangement No. c 13 -98	Number of contacts Size contacts Service rating Contact location Supersedes 10 20 I All MS20051-86				
						SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o (professional recommenda
N						Count FR
						PN: 8D513\
						16 First Release
_					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumir
<u>→</u>					SCALE NA	General linear Tolerances: ±
					SOURIA	U WWW.SOURIAU.C
					FORMAT A3	SOURIAU 8DE12M
L	Н	G	F	E	D	8D513W

	Φ		А				
					4		
					3		
whic r of the datio	n, technical n	mply with by a third party	l List		2		
		CUSTOMER D		MOD N°			
ninium Plug 8D series							
ır	NPRDS / PROJECT						
859 This document is the property of							
.COM		SOURIAU it must not be reproduced or communicated without permission					
U DRG N° SHEET							
W98BB-C 2/2							
	В		А				