

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
GP	00	B	REVISED PER ECO-11-006475	19OCT2011	CJV/CWR

1 PLUG ACCEPTS 22 DF PIN CONTACTS. CONTACTS MUST BE PURCHASED SEPARATELY.  
 2. ALL PARTS SHIPPED UNASSEMBLED.  
 3 FLAME RETARDANT 94V-0 RATED, STYRENE POLYOLEFIN OR PVC, BLACK.  
 4 FLAME RETARDANT 94V-0 RATED GLASS FILLED, NYLON OR POLYESTER, BLACK.  
 5 CARBON STEEL.  
 6 .000200 MIN. TIN PLATE OVER .000100 MIN. COPPER UNDERPLATE.  
 7 ELECTRODEPOSITED POLYURETHANE, BLACK.  
 8 COMPONENTS INDIVIDUALLY BULK PACKED.  
 9 ZINC ALLOY.

EXPANDING NECK ACCOMMODATES CABLE FROM .190-.375 DIA

1.355 MAX

FERRULE (MUST BE PURCHASED SEPARATELY AS REQD BY CABLE DIA)

4-40 JACKSCREW QTY:2

.125 MAX

SHIELD QTY:2

1.467 TYP

.812 TYP

ENCLOSURE

HDP-22 PLUG CONNECTOR

.630 MAX

CABLE REF

1.640 MAX

.984

8	W/ LOGOS	1658678-1
PACKAGING	REMARKS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L. BAUM 02JAN04		
DIMENSIONS: INCHES		CHK S. BOLASH 02JAN04		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M. WALMSLEY 02JAN04	NAME	
0 PLC ± -		PRODUCT SPEC	SHIELDING ENCLOSURE KIT, PLUG, SIZE 1, 15 POSN, HDP-22, AMPLIMITE™	
1 PLC ± -		APPLICATION SPEC	SIZE CAGE CODE DRAWING NO RESTRICTED TO	
2 PLC ± -		108-1268	A2 00779 C-1658678	
3 PLC ± .005		114-10001	SCALE 2:1 SHEET 1 of 1 REV B	
4 PLC ± -		WEIGHT -		
ANGLES ± 2°		CUSTOMER DRAWING		
FINISH				

1471-9 (3/11)