

Oct.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case that the application demands a high level of reliability, such as automotive,
 please contact a company representative for further information.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25 °C TO +85 °C	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C	
	VOLTAGE	_____	_____	_____	
	CURRENT	_____	APPLICABLE CABLE	φ 10±0.5mm	
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.		-	-	
ENVIRONMENTAL CHARACTERISTICS					
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 500 h.	NO HEAVY CORROSION RUIN THE FUNCTION.	X	-	
SEALING ⁽¹⁾	EXPOSED AT A DEPTH OF 1.8 m FOR 48 h.	NO WATER PENETRATION INSIDE CONNECTOR.	X	-	
AIRTIGHTNESS ⁽¹⁾	APPLY AIR PRESSURE 18 kPa FOR 0.5min TO INSIDE CONNECTOR.	NO AIR BUBBLES FROM INSIDE CONNECTOR.	X	-	
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
△					
REMARK			APPROVED	HY. KOBAYASHI	15.09.10
NOTE (1)SEALING AND AIRTIGHTNESS SHALL BE TESTED IN ASSEMBLED CONDITION WITH AN APPLICABLE CONNECTOR AND CABLE.			CHECKED	HY. KOBAYASHI	15.09.10
			DESIGNED	TH. KAMEYA	15.09.09
			DRAWN	TH. KAMEYA	15.09.09
Unless otherwise specified, refer to IEC 60512.					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.		ELC-110614-72-72	
HRS	SPECIFICATION SHEET		PART NO.	JR25WCC-10 (72)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL114-2064-5-72	△ 1/1