	T G	П	т	D	۰ ۳ ۳				
4	Z M Thread	ØF					4		
ယ					LAYOUT SHOWN AS EXAMPLE		3		
		Keying Shown as e	example						
	CHARACTERISTICSStandard : Based on MIL-DTL-38999 Series III	E	Connector dimensionDimNominalF22.25 Max						
	-Shell Material: Aluminium-Shell Plating: Black Zinc Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy		F22.25 MaxZ31.5 MaxVV THREADM18x1-6g		SOURIAU shall not be liable for any non-co due to a use of the Products which does the Specifications issued by either of the Par (professional recommendation, tech	s not comply with ties or by a third party			
N	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum				Country FR	Jurisdiction & Control List Not Listed	2		
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories				PN: 8D113Z98B	В			
	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours			A 27-09-20	A 27-09-2016 First Release				
_				ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	IOD N°		
				TITLE	Aluminium Inlin	e plug 8D series			
	BASIC SERIES: 8D 1 - 13 Z	98 B B		SCALE	General linear Tolerances:	NPRDS / PROJECT 859			
	SHELL TYPE : In line Receptacle CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13 CONTACT TYPE : SOCKET(500 Matings)				NA ± 859 SOURIAU WWW.SOURIAU.COM This document is the proper SOURIAU it must not be reproduced communicated without permit				
	PLATING : Z = Black Zinc Nickel		CONTACT LAYOUT : 1		SOURIAU DRO	6 N°	SHEET		
L	H G	F	E		8D113Z98BB	<u>-С</u> А	1/2		
			- V	_					

Г	Т	Q	г	m	D	C	Φ	А		
		Contact Layout								
4		$ \begin{array}{c} & & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & & \\ & & & \\ $								4
		Contacts Contact arrangement 13-98) Location X-axis position ID Y-axis (mm) A +.000 (0.00) +.195 (4.95) B +.125 (3.18) +.150 (3.81) C +.193 (4.90) +.030 (0.76) D 104 (4.17) 105 (2.67) E +.000 (0.00) 135 (3.43) F 164 (4.17) 105 (2.67) G 193 (4.90) +.030 (0.76) H 125 (3.18) +.150 (3.81) J +.085 (1.55) 015 (0.38)							-	
ω	Shell Arrangem no. 13 -98	K 065 (1.65) 015 (0.38) nt Number of contacts Size contacts Service rating Contact location Supersedes 10 20 I All MS20051-96								3
						SOURIAU shall not be liable for any r due to a use of the Products whic the Specifications issued by either of th (professional recommendatio	h does not comply wit ne Parties or by a thirc	:h		
N						Country FR PN: 8D113ZS	Jurisdiction & Not Lis			2
					A 27-09-2016 F ISS DATE Designed By:	First Release Latest modification - by Date:	CUSTO	DMER DRAWING	MOD N°	
					TITLE	Aluminium	Inline plug 8D s	series		
_					SCALE NA	General linear Tolerances: ±		RDS / PROJECT 859		1
					SOURIAU	WWW.SOURIAU.CC	M i	is document is the property SOURIAU t must not be reproduced c nmunicated without permis	or	
					FORMAT A3	SOURIAU E 8D113Z98	DRG N°		SHEET 2/2	
L	Н	G	F	E	D	C	B	A]	