ד ס ד	—		0	₽	Þ	
A						4
			LAYOUT SHOWN AS EX	KAMPLE		3
	own as example					
-Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal					
-Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum	ØS29.4 MaxZ31 MaxVV THREADM18x1-6g		SOURIAU shall not be liable for any due to a use of the Products wh the Specifications issued by either of (professional recommendat Country FR	ich does not comply with the Parties or by a third p ion, technical notice.)	party pontrol List	2
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories		PN: 8D513Z03SB				
-Temperature Range <u>:</u> -65°C to +175°C -Salt Spray : 500 hours		A 19-10-2016	First Release			_
		ISS DATE Designed By:	Latest modification - by	CUSTON	MOD N°	•
		TITLE	Date: CUSTOMER DRAWING Aluminium Plug 8D series			
BASIC SERIES: 8D 5 - 13 Z 03 S F SHELL TYPE : Plug with RFI Shielding	В	SCALE -{	General linear Tolerances:	-	S / PROJECT 859	_
CONTACT TYPE : Standard Crimp Contact		SOURIAU	WWW.SOURIAU.C	OM _{it}	document is the property of SOURIAU nust not be reproduced or	
SHELL SIZE : 13 PLATING : Z = Black Zinc Nickel	CONTACT TYPE : SOCKET(500 Matings) CONTACT LAYOUT : 13-03	FORMAT	SOURIAU		nunicated without permission SHEET	_
		A3	8D513Z(1/2	
			0202020		I	1

r	т	G	гт —	m	D		0	
		Contact Layout						
4		03						
		3#16 13-03						
	Ctc A B C	X Y 2.39 1.47 0 -2.79 -2.39 1.47						
ယ								
	1							
	F						the Specifications i	of the Products v
N								Coun
							Р	N: 8D513
					A 19-	-10-2016	First Release	
					ISS Designed By	DATE /:	Latest modification Date:	i - by
					тіт	LE		Alumi
					SCALE	-[$\square \bigcirc$	General linear Tolerances: ±
					SOUF	RIAU	WWW.	souriau.
					FORMAT A3			SOURIAU 8D5132

G

Н

F

Е

С

D

