



CONTACT CONFIGURATION

SWITCH FUNCTION		
PDS. 1	PDS. 2	PDS. 3
DN	NONE	DN
2-3-5-6	OPEN	2-1,5-4

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4 X.XX=±0.25
 3. TERM. NOS. FOR REF. ONLY
 4. RATING: 0.4(VA) max. @20V max. (AC or DC)
 5. FIXED TERM. & MOVING CONTACT: Copper alloy w/Gold plate over Nickel plate
 6. ELECTRICAL LIFE: 50,000 make-and-break cycles at full load.
 7. INSULATION RESISTANCE: 1000M ohm min.
 8. DIELECTRIC STRENGTH: 1000V RMS min. @seo level.
 9. OPERATING TEMP.: -30°C to 85°C



REV. A		11467		RELEASED FOR PRODUCTION		5/16/01		CJB	
REV. ECN No.		DESCRPTION		DATE		CHKD		TITLE	
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED		2004 WMDP-1 T2 A1 M6 R E		SCALE 2:1		DATE 5/16/01		DR CJB	
REV. A		T201110		DVG		REV			