Ξ			0	₿ ▶	
Image: state stat	ØF				4
			LAYOUT SHOWN AS EXAMP	LE	5
	Keying Shown as example				
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal]			
-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories	F35 MaxZ31.5 MaxVV THREADM31x1-6g		SOURIAU shall not be liable for any non- due to a use of the Products which do the Specifications issued by either of the P (professional recommendation, te <u>Country</u> FR PN: 8D121F41	bes not comply with Parties or by a third party echnical notice.) Jurisdiction & Control List Not Listed	2
-Temperature Range : -65°C to +200°C		A 23-09-201	L6 First Release		
-Salt Spray : 48 hours		ISS DATE	Latest modification - by		DD N°
		Designed By:	Date: Aluminium Inl	customer drawing ine plug 8D series	
BASIC SERIES: 8D 1 - 21 SHELL TYPE : In line Receptacle	F 41 P A	SCALE NA	General linear Tolerances: ±	NPRDS / PROJECT 859	1
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21	ORIEN CONTACT TYPE : PIN(50	SOURIAL	J WWW.SOURIAU.COM	This document is the property of SOURIAU it must not be reproduced or communicated without permission	
PLATING : F = Nickel	CONTACT LAY		SOURIAU DR	G N° SH	IEET
			8D121F41P	A-(1	1/2

	т	പ	н п	m		O	
		Contact Layout					
4		+Y 7 HOLES 31° 25' 27" 41'					
	\langle	20 HOLES					
		.835 Dia					
		Insert arrangement 21-41					
ယ		ber of Size Service Contact Supersedes tacts contacts rating location 11 20 I All MS20055-41					
\frown	-						
						SOURIAU shall not be liable due to a use of the Produ	
						the Specifications issued by e	ither c
						(professional recomr	nenda
N						F	Count FR
						PN: 8D2	121
					A 23-09-20	16 First Release	
					ISS DATE	Latest modification - by	
					Designed By:	Date:	
					TITLE	Alum	iniur
					SCALE	General I	inear
					NA		ces:
<u> </u>							
					SOURIA	U WWW.SOURIA	4U.C
					FORMAT	SOUR	
					A3	8D12	21F
	Н	G	F	E	D	C	
					V		

				4	
				3	
anv r	non-conformit	v or damage			
any non-conformity or damage which does not comply with r of the Parties or by a third party dation, technical notice.)					
ntry R	Jurisd	liction & Control List Not Listed	 	2	
1F4	41PA				
		CUSTOMER DRAWING	MOD N°		
um Inline plug 8D series					
r		NPRDS / PROJECT			
		859		1	
.CC	COM This document is the property of SOURIAU it must not be reproduced or				
111	DRG N°	communicated without pe	rmission SHEET		
	1PA-C		2/2		
<u>ат.</u>	B	A		J	

ω