ב 			0			
			LAYOUT SHOWN AS EXA	MPLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal ØS 25 Max	[-	
-Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy	Z 31 Max VV THREAD M15x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer		Country Jurisdiction & Control List				
-Contact Plating : Gold over copper Alloy 0.8μm minimum		FR Not Listed				
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories		PN: 8D511W05AD				
-Temperature Range65°C to +175°C		A 17-10-2016				
-Salt Spray : 500 hours		ISS DATE	Latest modification - by		IOD N°	
Mass : 14.83 g ± 10%		Designed By:	Date:	CUSTOMER DRAWING		
				TITLE Aluminium Plug 8D series		
BASIC SERIES: 8D 5 - 11 W 05	AD	SCALE	General linear	NPRDS / PROJECT		
SHELL TYPE : Plug with RFI Shielding		NA	Tolerances:	859		
CONTACT TYPE : Standard Crimp Contact ORIENTATION : D			This document is the property of		of	
SHELL SIZE : 11	SUURIAU	SOURIAU WWW.SOURIAU.COM it must not be reproduced communicated without permit				
PLATING : W = Olive drab Cadmium	CONTACT TYPE : PIN(500 Matings) CONTACT LAYOUT : 11-05		SOURIAU		SHEET	
		A3	8D511W0		1/2	
	1				-/-	

r	Ŧ	۵	н г	m		0
		Contact Layout				
4	-×_	$ \begin{array}{c} & & & \\ & $				
	Contai positi ID A B C C D E Shell Arrangement Numb size no. contai 11 -5 5	X-axis Y-axis (mm) +065 (1.65) +056 (1.42) +.113 (2.87) 065 (1.65) +.000 (0.00) 130 (3.30) 113 (2.87) 065 (1.65) 065 (1.65) +.056 (1.42) er of Size Service contacts rating Location				
ω		20 I All INS200303	1			
	F					SOURIAU shall not be liable for ar due to a use of the Products w the Specifications issued by either o
N						(professional recommenda Count FR PN: 8D511\
					A 17-10-20 ISS DATE Designed By:	016 First Release
					TITLE SCALE NA	Alumir General linear Tolerances: ±
					FORMAT A3	SOURIAU
	Н	G	F	E	D	8D511W

