		D	0	₿ >	
A Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z					
ω	the second secon		LAYOUT SHOWN AS EXAMI	PLE	
	Keying Shown as example				
CHARACTERISTICS	Connector dimension Dim Nominal	7			
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer	ØS 29.4 Max Z 31 Max VV THREAD M18x1-6g		SOURIAU shall not be liable for any non due to a use of the Products which d the Specifications issued by either of the (professional recommendation, t	loes not comply with Parties or by a third party technical notice.)	
 Contact Plating : Gold over copper Alloy 0.8μm minimum 			Country FR	Jurisdiction & Control List Not Listed	
-Durability: 500 Mating cycles-Delivered with Souriau contacts and Accessories			PN: 8D513F03SD		
-Temperature Range _: -65°C to +200°C -Salt Spray : 48 hours		A 17-10-2016	5 First Release		
-Salt Spray : 48 hours		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	DD N°
		TITLE	TITLE Aluminium Plug 8D series		
BASIC SERIES: 8D 5 - 13 F SHELL TYPE : Plug with RFI Shielding	03 S D	SCALE	General linear Tolerances:	NPRDS / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13	ORIE CONTACT TYPE : SOCKET(!	NTATION : D SOUMAtings)	WWW.SOURIAU.COM	A This document is the property of SOURIAU it must not be reproduced or communicated without permission	
		/OUT : 13-03	SOURIAU DE		' IEET
PLATING : F = Nickel	CONTACT LA	A3			

	т	۵	ш п	т	D	0		
		Contact Layout						
4		3#16						
	Ctc A B	13-03 X Y 2.39 1.47 0 -2.79						
ى	С	-2.39 1.47						
	L							
						SOURIAU shall not be lia due to a use of the Pr the Specifications issued b (professional reco	roducts v oy either	
N						Coun FR		
						PN: 8	D513	
					A 17-10-2 ISS DATI Designed By:	016 First Release Latest modification - by Date:		
					TITLE		Alumi	
_					SCALE NA		eral linear erances: ±	
					SOURIA	U WWW.SOUI	RIAU.	
					FORMAT A3	SOL 8D	JRIAU 9513F	

G

Н

F

Е

D

С

