| 4 | | | | | | | | 4 |
|---|---|----------------------|--|---|-----------------------------|--------------|------------------------------|----|
| ω | | | | | LAYOUT SHOW | N AS EXAMPLE | | 3 |
| | Keying S | hown as example | | | | | | |
| | CHARACTERISTICS | Connector dimension | 1 | | | | | |
| | -Standard : Based on MIL-DTL-38999 Series III | DimNominalØS29.4 Max | | | | | | |
| - | -Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8μm minimum |] | SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed | | | | 2 | |
| | -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories | | | PN: 8D513W04PA | | | | |
| | -Temperature Range -65°C to +175°C | | | A 19-10-2016 | First Release | | | |
| | -Salt Spray : 500 hours -Mass : 21.04 g ± 10% | | 1 | SS DATE | Latest modification - by | | MOD N | v. |
| | -Mass : 21.04 g ± 10% | | | signed By: | Date: | CUS | TOMER DRAWING | |
| | | | | TITLE | Aluminium Plug 8D series | | | |
| - | BASIC SERIES: 8D 5 - 13 W 04 P SHELL TYPE : Plug with RFI Shielding - 13 W 04 P | A | | SCALE - | General li Tolerand ± | | PRDS / PROJECT 859 | 1 |
| - | CONTACT TYPE : Standard Crimp Contact ORIENTATION | | | SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or | | | | |
| - | SHELL SIZE : 13 CONTACT TYPE : PIN(500 Matir | | | FORMAT SOURIAU DRG N° SHEET | | | | |
| - | PLATING : W = Olive drab Cadmium | CONTACT LAYC | 501.15-04 | A3 | | | 1/2 | |
| | H G F | E | / D | | C C | 3W04PA-C | A | |

| - | Ŧ | G | н г | m | D | 0 |
|---|---|---|------------|---|------------------------|---|
| | | Contact Layout | | | | |
| 4 | ٠ | $ \begin{array}{c} $ | | | | |
| | Conta position A B C D Shell Arrangement N size no. d 13 -4 | +.000 (0.00) +.150 (3.81) +.146 (3.71) +.035 (0.89) +.000 (0.00) 083 (2.11) 146 (3.71) +.035 (0.89) | | | | |
| ယ | | | | | | |
| | _ | | | | | |
| 7 | | | | | | SOURIAU shall not be liable for an due to a use of the Products wh the Specifications issued by either o (professional recommendat |
| N | | | | | | Countr FR |
| | | | | | | PN: 8D513V |
| | | | | | A 19-10-20 ISS DATE | 16 First Release Latest modification - by |
| | | | | | Designed By: | Date: |
| | | | | | TITLE | Alumin |
| _ | | | | | SCALE | General linear Tolerances: |
| | | | | | SOURIA | U WWW.SOURIAU.C |
| | | | | | FORMAT A3 | SOURIAU |
| L | Н | G | F | E | D | 8D513W |

