	m I		0	B		
ØS-						
			LAYOUT SHOWN AS EXAN	ЛРLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension]				
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal ØS 25 Max					
-Shell Material : Aluminium -Shell Plating : Nickel	Z 31 Max]	SOURIAU shall not be liable for any no			
-Insulator : Thermoplastic	VV THREAD M15x1-6g	J	due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party			
-Contacts : Copper Alloy			(professional recommendation	, technical notice.)		
-Seals & Grommet : Silicon Elastomer		L	Country	Jurisdiction & Control List	1	
-Contact Plating : Gold over copper Alloy 0.8µm minimum			FR	Not Listed		
-Durability : 500 Mating cycles						
-Delivered with Souriau contacts and Accessories			PN: 8D511F0	47C		
-Temperature Range <u>-</u> -65°C to +200°C		A 15-10-2016	First Release			
-Salt Spray : 48 hours						
Mass : 14.8 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	
		TITLE	Aluminiu	m Plug 8D series		
		SCALE	General linear			
BASIC SERIES: 8D 5 - 11 F	04 P E	- -	Tolerances:	NPRDS / PROJECT 859		
SHELL TYPE : Plug with RFI Shielding		NA		This document is the prop	erty of	
CONTACT TYPE : Standard Crimp Contact	ORIE	NTATION : E SOURIAU	WWW.SOURIAU.CO	COUDIALI		
SHELL SIZE : 11	CONTACT TYPE : PIN(5			communicated without per		
PLATING : F = Nickel	CONTACT LAY	VOUT : 11-04 FORMAT	SOURIAU D	RG N°	SHEET	
			8D511F04		1/2	

ſ	Ξ	۵	г П	m		0	
		Contact Layout					
4	y.	$ \begin{array}{c} $					
	Shell Arrangement Numb size no.	X-axis (mm) Y-axis (mm) +.065 (1.65) +.065 (1.65) +.065 (1.65) 065 (1.65) 065 (1.65) 065 (1.65) 065 (1.65) +.065 (1.65) 065 (1.65) +.065 (1.65) 065 (1.65) +.065 (1.65) 065 (1.65) +.065 (1.65) 065 (1.65) +.065 (1.65) 065 (1.65) +.065 (1.65) 065 (1.65) +.065 (1.65) 065 (1.65) +.065 (1.65)]				
ω			-				
	1						
						SOURIAU shall not be liable for ar due to a use of the Products w the Specifications issued by either o (professional recommenda	
N						Count FR	
						PN: 8D511	
					ISS DATE	16 First Release Latest modification - by Date:	
					Designed By:	Alumir	
<u> </u>					SCALE	General linear Tolerances:	
					SOURIA	SOURIAU WWW.SOURIAU.	
					FORMAT A3	SOURIAU 8D511F	
L	Н	G	F	E	D	C	

