	T G	т п	D	0	د م	>
Control Control Laboration of Control Laboratio Control Laboration of Control Laboration of Control L						-
Shell Material : Aluminium Shell Material : Aluminium Shell Material : Black Zinc Nickel - Insulator : Thermoplastic - Shell Material : Compare Alloy - Seals & Grommet : Silicon Elastomer - Contact Plaing : Gold over copper Alloy 0.8µm minimum - Ourisolity : Sou Maing cycles - Delivered with Souriau contacts and Accessories - - Temperature Range : 65° C to +175°C - Salt Spray : Sou Naing cycles - Delivered with Souriau contacts and Accessories - - Temperature Range : 65° C to +175°C - Salt Spray : Sou Nouris - Mass : 17.15 g ± 10% ORIENTATION: C CONTACT TYPE: Standard Crimp Contact SHELL TYPE : Plug with RFI Shielding - CONTACT TYPE: Standard Crimp Contact Souriau SHELL SIZE : 11 - PLATING : Z = Black Zinc Nickel CONTACT TYPE: SOCKET(500 Mating) Yeard SOURIAU DRG N°		Connector dimension]	LAYOUT SHOWN AS EXAMPL	LE	
-Delivered with Souriau contacts and Accessories -Temperature Range : .65°C to +175°C -Salt Spray : .500 hours -Mass : .17.15 g ± 10% BASIC SERIES: .8D 5 11 Z 02 B C SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 PLATING : Z = Black Zinc Nickel CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : STandard Crimp Contact SHELL SIZE : 11 PLATING : Z = Black Zinc Nickel CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Matings) PLATING : Z = Black Zinc Nickel CONTACT TYPE : SOCKET(500 Matings) ORIENTATION :C SOURIAU DRG N° SHEET	-Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum	ØS 25 Max Z 31 Max		due to a use of the Products which do the Specifications issued by either of the Pro- (professional recommendation, te Country	bes not comply with arties or by a third party echnical notice.) Jurisdiction & Control List	
BASIC SERIES: 8D 5 - 11 Z 02 B C SCALE S	-Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		ISS DATE	First Release Latest modification - by		
CONTACT TYPE : Standard Crimp Contact ORIENTATION : C SOURIAU SOURIAU.COM SOURIAU.com it must not be reproduced or communicated without permission SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) CONTACT LAYOUT : 11-02 FORMAT SOURIAU SOURIAU.com SOURIAU SOUR		02 B C	SCALE	General linear Tolerances:	NPRDS / PROJECT 859	
A3 8D511Z02BC-C 1/2	SHELL SIZE : 11	CONTACT TYPE : SOCKET(5	00 Matings)	SOURIAU DR	SOURIAU it must not be repro communicated withou	oduced or t permission

	Ŧ	G	н г	m		0	
		Contact Layout					
4	. x. 0. (2)	+Y IB IA +Y +X 95 4(mm) (2.4(mm))					
	Cont positi III A B Shell Arrangement size no. 11 -2	tion X-axis Y-axis (mm) (mm) +.095 (2.41) +.000 (.00)					
ω							
	L						
						SOURIAU shall not be liab due to a use of the Pro the Specifications issued by (professional recon	ducts w either o
N							Count FR
						PN: 8D)511
					A 18-10-20	16 First Release	
_					ISS DATE Designed By:	Latest modification - by Date:	
					TITLE	Δ	lumi
_					SCALE NA	Genera Tolera ±	ances:
					SOURIA	U WWW.SOUR	IAU.(
					FORMAT	SOU	RIAL
l	Н	G	F	E	A3	8D5	511Z
	П	I G					

