



RECOMMENDED LAYOUT FOR
.125 THICK P.C. BOARD

1. PARTS COMPLY WITH AMP SOLDERABILITY
SPEC. NO. 109-11-3

DIMENSIONS IN INCHES. DO NOT SCALE PRINT.

| | | | |
|-----------------|----------------|----------------|------|
| REVISION RECORD | REV. | DESCRIPTION | DATE |
| M | 085 | 9-1 PER CM-760 | |
| N | PER EN CM-2109 | | |
| | | ABSOLETE -2 | |

NUMBER 350423

| DESCRIPTION | REQUIRED PER ASSEMBLY |
|-------------|-----------------------|
| | |
| | |
| | |

| | | |
|--|--|--|
| ASSEMBLY NO. 350423-1 NYLON - NATURAL HSG. MATL & COLOR PIN MATL & FINISH COPPER ALL OV - PRE-TIN | | SEE TABLE WIRE - GAUGE - INSULATION TOLERANCE EXCEPT AS NOTED 3 CIRCUIT P.C. BOARD MATE-N-LOK |
| MATERIAL AND FINISH AMP INCORPORATED MADE IN U.S.A. | | LOC B NO 350423 N |

AMP PRODUCTS COVERED BY PATENTS AND/OR PATENTS PENDING.
© 1975 AMP INCORPORATED. ALL RIGHTS RESERVED.
9. Edman
6-25-75

