APPLIC	ĴΑĿ	SLE STANI	DAKD										
		OPERATING FEMPERATUR	-35°C TO 85°C (NOTE 1)			STORAGE TEMPERATURE RANGE		E	-10°C TO 60°C				
RATING	3 \	/OLTAGE	30V AC				LICABLE			BM14C (0. 8) -28DS-0.		4V (**)	
		CURRENT	0. 3A										
		JORREIVI		SPEC	IFICA	ATIO	NS						
	ITE	:M		TEST METHOD	11 10/	1110		R	FOLL	IREMENTS	QT	АТ	
CONST		JCTION		TEST WETTOD				- 11	LQU	IICLIVICIVIO	QΙ	^	
			VISUALL	Y AND BY MEASURING IN	STRUMI	ENT.	ACCO	RDING T	O DR	RAWING.	Х	Х	
MARKING	3		CONFIRMED VISUALLY.								X	X	
ELECT	RIC	CHARA	CTERISTICS										
			20mV AC OR LESS 1kHz,1mA .				100mΩ MAX.				Х	_	
INSULATION RESISTANCE			100V DC.			50MΩ MIN.				Х	<u> </u>		
VOLTAGE PROOF			100V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.				Х	<u> </u>	
MECH	ΔΝΙΙ	CAL CHA	RACTE	ERISTICS							^		
MECHAN				SINSERTIONS AND EXTRA	CTIONS	<u> </u>	① CO	NTACT F	PESIS	STANCE: 100mΩ MAX.	I		
OPERATION			To time a moeth form of the first of the fir				② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.				X	_	
VIBRATION			FREQUENCY 10 TO 55 TO 10 Hz,APPROX 5min, SINGLE AMPLITUDE 0.75 mm,10CYCLES,				① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF				Х	-	
			FOR 3 DIRECTIONS. 490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES				PARTS.						
SHOCK			FOR 3 DIRECTIONS.				② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.					_	
ENVIR	ON	MENTAL	CHARA	ACTERISTICS									
RAPID CHANGE OF TEMPERATURE			TEMPERATURE -55 → +85°C TIME 30 → 30 min				① COI	NTACT F	RESIS	STANCE: 100mΩ MAX.			
							_			SISTANCE: $50M\Omega$ MIN.	X	-	
			UNDER 5 CYCLES. (RELOCATION TIME TO CHANBER: WITHIN 2-3 min)					DAMAG PARTS.	E, CF	RACK OR LOOSENESS			
DAMP HEAT (STEADY STATE)			EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.			① CONTACT RESISTANCE: $100m\Omega$ MAX. ② INSULATION RESISTANCE: $25M\Omega$ MIN.				Х			
											-		
							③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.						
SULPHUR DIIOXIDE			EXPOSED IN 25 PPM FOR 96h,25°C,75%.			 CONTACT RESISTANCE: 100mΩ MAX. NO EVIDENCE OF CORROSION WHICH AFFECTS TO OPERATION OF CONNECTOR. 				\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			
			(REFER TO JIS C 60068)							X	_		
							NED OUTSYS					<u> </u>	
COL	UNT	DE	DESCRIPTION OF REVISIONS DES			DESIG	GNED CHECKED					TE	
REMARKS	S							APPRO'	VED	MO. ISHIDA	16.0)5. 09	
NOTE1: INCLUDE THE TEMPE			ERATURE RISING BY CURRENT				CHECK		TS. MIYAZAKI)5. 09)5. 09		
			ied, refer to JIS C 5402 and IEC 60512.					DESIGN		NY. YAMASHIRO)5. 09	
Unless o	the	wise specifi					DRAWN			SN. NUMAZAKI	16. 04. 28		
Note QT:Qualification Test AT:Assurance Test X:Applicable Test DRAWING NO.							ELC-324417-5	•					
RS	5	SPECIFICATION SHEET PA				PART	NO. BM14C (0.8) -28DP-0.4V			(51)			
		HIR	OSE EI	LECTRIC CO., LTD.	CTRIC CO., LTD.		CODE NO.		CL684-8027-3-51		Δ	1/1	