


RECOMMEND P.C.B. LAYOUT

**OBSOLETE**  
 February 2017  
 PCR 22710



CIRCUIT: SPDT

CONTACT CONFIGURATION

SWITCH FUNCTION		
PDS. 1	PDS. 2	PDS. 3
ON	OFF	<DN>
2-3	OPEN	2-1

(< )=Momentary

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: 0.0=±0.4  
0.00=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 0.4VA Max. @20V Max. (AC or DC)
5. ELECTRICAL LIFE: 30,000 make-and-break cycles at full load.
6. INSULATION RESISTANCE: 1000M ohm min.
7. DIELECTRIC STRENGTH: 1,000 V RMS @sea level.
8. OPERATING TEMP.: -30°C to 85°C

**E-SWITCH®**

TITLE					300A WSP-5 J6 VS2 R E				
SCALE	2:1	DATE	3/7/00	DR	MM	DWG	T301502	REV	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

A	10559	RELEASED FOR PRODUCTION	3/7/00	MM
REV.	ECN No.	DESCRIPTION	DATE	CHKD