	LAYOUT SHOWN AS EXAMI	PLE		
Keying Shown as example				
-Standard : Based on MIL-DTL-38999 Series III Connector dimension				
Shell Material Aluminium	SOURIAU shall not be liable for any non		7	
-Shell Plating : Nickel VV THREAD M22x1-6g	due to a use of the Products which does not comply with			
-Insulator : Thermoplastic	the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Contacts : Copper Alloy	(professional recommendation, t	.כנוווונמו ווטנונכ.)		
-Seals & Grommet : Silicon Elastomer	Country	Jurisdiction & Control List		
-Contact Plating : Gold over copper Alloy 0.8µm minimum	FR	Not Listed		
-Durability : 500 Mating cycles	PN: 8D515F05SC			
-Delivered with Souriau contacts and Accessories				
-Temperature Range -65°C to +200°C	9-10-2016 First Release			
-Salt Spray     : 48 hours       -Mass     : 31.38 g ± 10%	DATE Latest modification - by		MOD N°	
Designed By:		CUSTOMER DRAWING		
ттт	ITLE Aluminium	Aluminium Plug 8D series		
	General linear	NPRDS / PROJECT		
BASIC SERIES. 80 5 - 15 F 05 5 C		859		
SHELL TYPE : Plug with RFI Shielding     NA		This document is the property	y of	
CONTACT TYPE : Standard Crimp Contact ORIENTATION : C SOUR	SOURIAU       WWW.SOURIAU.COM       SOURIAU         Souriau       it must not be reproduced or communicated without permission			
SHELL SIZE : 15 CONTACT TYPE : SOCKET(500 Matings)				
PLATING :     F =     Nickel       FORMAT     CONTACT LAYOUT : 15-05     FORMAT	JUUNAU DI	₹G N°	SHEET	
A3	8D515F055	SC-C	1/2	

					1	
	<b>工</b>	G	п П	m	D	0
4		Contact Layout $ \begin{pmatrix} \bullet & \bullet \\ \bullet & \bullet \\\bullet \\\bullet & \bullet \\\bullet \\$				
		X-axis (mm)         Y-axis (mm)           +.000 (0.00)         +.100 (2.54)           +.174 (4.42)         +.024 (0.61)           +.094 (2.39)        148 (3.76)          094 (2.39)        148 (3.76)          174 (4.42)         +.024 (0.61)				
ω						
						SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o (professional recommenda
N						Count
						PN: 8D515
						016 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumir
<u> </u>					SCALE NA	General linear Tolerances:
					SOURIA	U WWW.SOURIAU.C
					FORMAT A3	SOURIAU
	H	G	F	E		8D515F
					$\vee$	

