

SUGGESTED PANEL CUTOUT

MATERIALS

BODY:
Polyamide 6/6 (PA66), UL94 V-2

ACTUATOR:
Polyamide 6/6 (PA66), UL94 V-2

SEALING MEMBRANE:
Polyvinyl Chloride (PVC)

SPRING:
Phono wire

MOBILE CONTACT BAR:
Copper

CONTACT PADS:
Silver Clad Copper

RIFETS:
Copper

TERMINALS:
Silver Plated Brass

SPECIFICATIONS

FUNCTION:
2PT OFF-(ON)

RATINGS:
ANSI/UL 508 and CAN/CSA C22.2 No.14 (E198908):
15A 277VAC [cULRu]
15A 277VAC [cULRu]
15HP 110/250VAC [cULRu]

CONTACT RESISTANCE:
Initial: 10mΩ Max.
Electrical Life: [cULRu]
6,000 Cycles [cULRu]

TEMPERATURE:
Operating: 0°C to 40°C [cULRu]

INGRESS PROTECTION:
IP54

COLORS AND MARKINGS



BODY COLOR:
Black

ACTUATOR COLOR:
White

MARKING:
None

MARKING COLOR:
None

SCHEMATIC



RWVG4ED1200

DRAWING NUMBER: 34-RWVG4ED1200
DATE: DECEMBER 9, 2009
REVISION: C

ACTUATOR	B	10/05/28	CAB
BODY	A <td>09/07/28 <th>CAB</th> </td>	09/07/28 <th>CAB</th>	CAB
COLORS	A <td>09/07/28 <th>CAB</th> </td>	09/07/28 <th>CAB</th>	CAB
MATERIALS	C <td>10/03/07 <th>CAB</th> </td>	10/03/07 <th>CAB</th>	CAB
SPECIFICATIONS	C <td>10/03/07 <th>CAB</th> </td>	10/03/07 <th>CAB</th>	CAB
REFERENCE	REV. <td>DATE</td> <td>BY</td>	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED

REV.	DESCRIPTION	DATE	BY
C	CORRECTED HP SPECIFICATION, was 2.0HP	02/18/13	TC
B	CORRECTED SPECIFICATIONS	09/12/09	CAB
A	INITIAL RELEASE	09/07/28 <td>CAB</td>	CAB

DIMENSIONS	
INCHES [MILLIMETERS]	
GENERAL TOLERANCES	±0.008 [±0.2] / ±1°
SCALE	DRAWING NOT TO SCALE
PROJECTION	DRIVING NUMBER