	т Q I	m		0	₩	≻	
CHARCTERISTICS Standard: Based on MLDT-138999 Series III: Stell Material :: Connector direction Stell Material :: Connector direction Stell Material :: Stell Material :: Stell Sprix Stell Material :: Material Sprix Stell Material :: Stell Material ::	4						
CHARACTERSTICE Sundard: Based on MIL-DTL38999 Series III Sundard: Based on MIL-DTL38999 Series III Sundard: Based on MIL-DTL38999 Series III Sundard: Standard Ching Contacts Scontacts Scontact Baing Contact Paining Scontact Baing Scontact Baing Scontact Paining S				LAYOUT SHOWN AS E	XAMPLE		
CHARACTERSTICE Sundard: Based on MIL-DTL38999 Series III Sundard: Based on MIL-DTL38999 Series III Sundard: Based on MIL-DTL38999 Series III Sundard: Standard Ching Contacts Scontacts Scontact Baing Contact Paining Scontact Baing Scontact Baing Scontact Paining S	Keying	Shown as example					
Standard : Based on MiL/DTL-38999 Series III Shell Material ::::::::::::::::::::::::::::::::::::							
-Shell Matters ::::::::::::::::::::::::::::::::::::							
- Durability :: 500 Mating cycles - Delivered with Souriau contacts and Accessories - Temperature Range :: 65°C to +175°C - Salt Spray :: 500 hours - Mass :: 60.18 g ± 10% BASIC SERIES: 80 SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21 ORIENTATION : N CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21 : CONTACT TYPE : Standard Crimp Contact PLATING : W = Olive drab Cadmium	-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer	Shell MaterialÁluminiumÓS41.7 MaxShell PlatingC live drab CadmiumZ31 MaxShell PlatingOlive drab CadmiumVV THREADM31x1-6gInsulatorThermoplasticVV THREADM31x1-6gSouractsCopper AlloyCopper AlloyCountryJurisdiction & Control List					
-Salt Spray : 500 hours -Mass : 60.18 g ± 10% BASIC SERIES: <u>8D</u> 5 - <u>21</u> W 41 <u>B</u> N <u>CONTACT TYPE</u> : Standard Crimp Contact <u>SHELL SIZE : 21</u> <u>PLATING : W = Olive drab Cadmium</u> <u>CONTACT TYPE : SOCKET(500 Matings)</u> <u>CONTACT TYPE : SOCKET(500 Matings)</u> <u>1/2</u> <u>CONTACT TYPE : SOCKET(500 Matings)</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1/2</u> <u>1</u>	-Durability : 500 Mating cycles						
-Salt Spray : 500 hours -Mass : 60.18 g ± 10% -Mass : 60.18 g ± 10% BASIC SERIES: 8D 5 - 21 W 41 B N CONTACT TYPE : Slandard Crimp Contact SHELL SIZE : 21 PLATING : W = Olive drab Cadmium CONTACT TYPE : SOCKET(S00 Matings) PLATING : W = Olive drab Cadmium CONTACT TYPE : SOCKET(S00 Matings) PLATING : W = Olive drab Cadmium CONTACT TYPE : SOCKET(S00 Matings) PLATING : W = Olive drab Cadmium CONTACT TYPE : SOCKET(S00 Matings) PLATING : W = Olive drab Cadmium CONTACT TYPE : SOCKET(S00 Matings) PLATING : W = Olive drab Cadmium CONTACT TYPE : SOCKET(S00 Matings) PLATING : W = Olive drab Cadmium CONTACT TYPE : SOCKET(S00 Matings) PLATING : W = Olive drab Cadmium CONTACT TYPE : SOCKET(S00 Matings) PLATING : W = Olive drab Cadmium CONTACT TYPE : SOCKET(S00 Matings) CONTACT TYPE : SOCKET(S00 Matin	-Temperature Range : -65°C to +175°C		A 10-10-2016	First Release			
BASIC SERIES: 8D 5 21 W 41 B N BASIC SERIES: 8D 5 21 W 41 B N CONTACT TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21 NPRDS / PROJECT Stell Size : 21 This document is the property of SOURIAU SOURIAU SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU SOURIAU it must not be reproduced or communicated without permission PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 21-41 FORMAT SOURIAU DRG N° SHEET A3 8D521W41BN-C 1/2							
BASIC SERIES: 8D 5 - 21 W 41 B N SCALE Tolerances: 359 SHELL TYPE : Standard Crimp Contact ORIENTATION : N NA SOURIAU This document is the property of SOURIAU SOURIAU it must not be reproduced or communicated without permission SHELL SIZE : W = Olive drab Cadmium CONTACT TYPE : SOCKET(500 Matings) CONTACT LAYOUT : 21-41 FORMAT SOURIAU DRG N° SHEET A3 8D521W41BN-C 1/2					CUSTOMER		
BASE SENES: BUILSTYPE: BUILSTYPE: SUBJICT SUBJ			TITLE Aluminium Plug 8D series				
CONTACT TYPE : Standard Crimp Contact ORIENTATION : N SOURIAU SOURIAU.COM it must not be reproduced or communicated without permission SHELL SIZE : 21 CONTACT TYPE : SOCKET(500 Matings) CONTACT LAYOUT : 21-41 FORMAT SOURIAU DRG N° SHEET PLATING : W = Olive drab Cadmium CONTACT CATOR CONTACT LAYOUT : 21-41 FORMAT SOURIAU DRG N° SHEET 1/2 Image: Souriau Contact Cadmium Image: Souriau Contact Cadmium Image: Souriau Contact Cadmium SHEET		N		Tolerances:	85	9	
PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 21-41 FORMAT SOURIAU DRG N° SHEET A3 8D521W41BN-C 1/2			- SUUKIAU	SOURIAU WWW.SOURIAU.COM SOURIAU it must not be reproduced or			
A3 8D521W41BN-C 1/2			-				
	PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 21-4	±				
	H G F	E		8D521W	41BN-C	A	

	т	പ	п –	m		O
		Contact Layout				
4		+Y 7 HOLES				
	<	31 23 37 41				
		A A A A A A A A A A A A A A A A A A A				
	Shell Arrangement Numl size no. cont	Insert arrangement 21-41 ber of Size Service Contact Supersedes tacts contacts rating location				
ω	21 -41 4	11 20 I All MS20055-41				
-	—					
						SOURIAU shall not be liable for a due to a use of the Products w
						the Specifications issued by either (professional recommend)
						(professional recommenda
N						Coun FR
						PN: 8D521
					A 10-10-20	116 First Release
					ISS DATE	
					Designed By:	Date:
					TITLE	Alumi
					SCALE	General linear Tolerances:
<u> </u>					NA	
					SOURIA	U WWW.SOURIAU.
					FORMAT	SOURIAL
		T	1		A3	8D521W
	Н	G	l F	E	D	C

