



NOTES:

1. HARDWARE IS INCLUDED.
2. PRE-FLATTEN/NOTCH DIMENSIONS ARE:
 TOP: .386 ± .010
 BOTTOM: .448 ± .010

BUSHING FINISH	SILVER
LEAD FINISH	SOLDER
CAPACITANCE	1000pF +100/-0%
TEMP. RANGE	-55°C/+125°C
CURRENT	25 AMPS
WORKING VOLTAGE	125°C 500 VDC
DC RESISTANCE	.01 Ohms MAX.
IL=PER MIL-STD-220	
FREQ. MHz	I.L. (db)
100MHz	15
300MHz	25
1 GHz	35
10 GHz	40
SCHEMATIC	
MARKING:	
PART: 102P	
BAG:	
SCI 54-806-002 102P	
DATE CODE	
LOT NO.	
QTY/BAG	

			01	0	REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED		FAIRVIEW PENNSYLVANIA
			CN 26142-CPD	REDRAWN	CHANGE NOTICE	Fractions ± 1/64		
			CN 185171			Dec. .xx±	Dwn. KAUFFMAN	Description
						Dec. .xxx± .010	Date 3-9-06	FLTR., SING., FT, BSHG.
						Angles ±0° 30'	Engr. STRUCHEN	54806002X5V102P
						CODE IDENT. NO. DLSP2	Scale NONE	