


H G F E D C B A

4
3
2
1

4
3
2
1



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

| Connector dimension | |
|---------------------|----------|
| Dim | Nominal |
| F | 35 Max |
| Z | 31.5 Max |
| VV THREAD | M31x1-6g |

CHARACTERISTICS

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Aluminium
- Shell Plating : Olive drab Cadmium
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered with Souriau contacts and Accessories
- Temperature Range : -65°C to +175°C
- Salt Spray : 500 hours

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR | Not Listed |

PN: 8D121W39BA

| | | | |
|--------------|------------|--------------------------|-------------------------|
| A | 24-09-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |


| | | | | | | | | | |
|----------------|------------------------|---|---|----|------------------------|----|------------------------------------|---|--|
| BASIC SERIES: | 8D | 1 | - | 21 | W | 39 | B | A | |
| SHELL TYPE : | In line Receptacle | | | | | | | | |
| CONTACT TYPE : | Standard Crimp Contact | | | | | | | | |
| SHELL SIZE : | 21 | | | | | | | | |
| PLATING : | W = Olive drab Cadmium | | | | | | | | |
| | | | | | ORIENTATION : A | | CONTACT TYPE : SOCKET(500 Matings) | | |
| | | | | | CONTACT LAYOUT : 21-39 | | | | |

| | | | |
|----------------|---------------------------------|--------------------------------|---|
| TITLE | Aluminium Inline plug 8D series | | |
| SCALE | NA | General linear Tolerances: ±-- | NPRDS / PROJECT 859 |
| SOURIAU | WWW.SOURIAU.COM | | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT | A3 | | SOURIAU DRG N° 8D121W39BA-C |
| | | | SHEET 1/2 |

H G F E D C B A

4
3
2
1

Contact Layout



Contacts
(Insert arrangement 21-39)

| Contact position ID | Location | | Contact position ID | Location | |
|---------------------|--------------|--------------|---------------------|-------------|-------------|
| | X-axis (mm) | Y-axis (mm) | | X-axis (mm) | Y-axis (mm) |
| A | +065 (1.65) | +411 (10.44) | X | +000 (0.00) | +295 (7.49) |
| B | +189 (4.80) | +371 (9.42) | Y | +126 (3.20) | +256 (6.50) |
| C | +294 (7.47) | +294 (7.47) | Z | +232 (5.89) | +179 (4.55) |
| D | +371 (9.42) | +189 (4.80) | a | +280 (7.11) | +057 (1.45) |
| E | -411 (10.44) | +065 (1.65) | b | -280 (7.11) | -074 (1.88) |
| F | +411 (10.44) | -065 (1.65) | c | +217 (5.51) | -189 (4.80) |
| G | +371 (9.42) | -189 (4.80) | d | +112 (2.84) | -265 (6.73) |
| H | +294 (7.47) | -294 (7.47) | e | -112 (2.84) | -265 (6.73) |
| J | +189 (4.80) | -371 (9.42) | f | -217 (5.51) | -189 (4.80) |
| K | +065 (1.65) | -411 (10.44) | g | -280 (7.11) | -074 (1.88) |
| L | -065 (1.65) | -411 (10.44) | h | -280 (7.11) | +057 (1.45) |
| M | -189 (4.80) | -371 (9.42) | i | -232 (5.89) | +179 (4.55) |
| N | -294 (7.47) | -294 (7.47) | l | -126 (3.20) | +256 (6.50) |
| P | -371 (9.42) | -189 (4.80) | k | +000 (0.00) | +164 (4.17) |
| R | -411 (10.44) | -065 (1.65) | m | +114 (2.90) | +048 (1.22) |

Contacts
(Insert arrangement 21-39)

| Contact position ID | Location | | Contact position ID | Location | |
|---------------------|--------------|--------------|---------------------|-------------|-------------|
| | X-axis (mm) | Y-axis (mm) | | X-axis (mm) | Y-axis (mm) |
| S | -411 (10.44) | +065 (1.65) | n | +106 (2.69) | -107 (2.72) |
| T | -371 (9.42) | +189 (4.80) | p | +000 (0.00) | -189 (4.80) |
| U | -294 (7.47) | +294 (7.47) | q | -106 (2.69) | -107 (2.72) |
| V | -189 (4.80) | +371 (9.42) | r | -114 (2.90) | +048 (1.09) |
| W | -065 (1.65) | +411 (10.44) | --- | --- | --- |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|--------------------|------------|
| 21 | -39 | 2 37 | 16 20 | I | f, m All others | MS20055-39 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR | Not Listed |

PN: 8D121W39BA

| | | | |
|----------------|------------------------------------|----------------------------|---|
| A | 24-09-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |
| TITLE | Aluminium Inline plug 8D series | | |
| SCALE | | General linear Tolerances: | NPRDS / PROJECT |
| NA | | ±-- | 859 |
| SOURIAU | WWW.SOURIAU.COM | | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT | SOURIAU DRG N° 8D121W39BA-C | | SHEET 2/2 |