

Device connector, rear mounting - RC-19P1NX2H0JS - 1602740

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



The figure shows the 12-pos. product version

Device connector for rear wall, straight, shielded: yes, Screw locking, M23, Axial O-ring, Central fastening M25 \times 1.5, Panel thickness min.: 0.8 mm, Panel thickness max.: 6.5 mm



Key Commercial Data

Packing unit	10 STK
GTIN	4 046356 241304
GTIN	4046356241304

Technical data

Housing data

Note	Order information: Order contact inserts separately
Housing material	Metal
Type of locking	Screw locking
Degree of protection (when plugged in)	IP67
Thread type	M23

Environmental Product Compliance


China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings



Device connector, rear mounting - RC-19P1NX2H0JS - 1602740

Dimensional drawing



Installation dimensions

Approvals

Approvais	
Approvals	
Approvals	
EAC	
Ex Approvals	
Approval details	
EAC EHL	B.01742

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com