	I G	т (г		0 0	
4	Z M Thread				
ω				LAYOUT SHOWN AS EXAMPLE	3
		Keying Shown as example			
	CHARACTERISTICS	Connector dimension			
	-Standard : Based on MIL-DTL-38999 Series III	DimNominalF25.4 Max			
	-Shell Material: Aluminium-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy	Z 31.5 Max VV THREAD M22x1-6g		SOURIAU shall not be liable for any non-confor due to a use of the Products which does no the Specifications issued by either of the Parties (professional recommendation, technica	t comply with or by a third party
N	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum			Country Ju FR	risdiction & Control List Not Listed 2
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D115F05AB	
	-Temperature Range _: -65°C to +200°C -Salt Spray : 48 hours		A 27-09-201	6 First Release	
_			ISS DATE Designed By:	Latest modification - by Date:	MOD N°
			TITLE	Aluminium Inline p	
	BASIC SERIES: 8D 1 - 15 F	05 A B	SCALE	General linear Tolerances:	NPRDS / PROJECT
→	SHELL TYPE : In line Receptacle		NA NA		859 This document is the property of
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 15		RIENTATION : B SOURIAL	WWW.SOURIAU.COM	SOURIAU it must not be reproduced or communicated without permission
	PLATING : F = Nickel		LAYOUT : 15-05	SOURIAU DRG N	
			A3	8D115F05AB-C	
	H I G I	F I E	D	C I B	I A

Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Inline plug 8D series SCALE Image: SCALE NA Image: SCALE SCALE Image: SCALE NA Image: SCALE SCALE Image: SCALE NA Image: SCALE SCALE Image: SCALE </th <th>B</th> <th></th> <th>m</th> <th>П</th> <th>۵</th> <th></th> <th>т</th> <th></th>	B		m	П	۵		т	
Image: Instant					B B B B B C C B C B C C C C C C C C C C C C C	$\begin{array}{c} & & & \\$		4
SOURIAU shull not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) PN: 8D115F05AB A 27-09-2016 first Release A 27-09-2016 first Release					148 (3.76) +.024 (0.61) Service Contact Supersedes rating location	D 094 (2.39) 148 E 174 (4.42) +.024 ement Number of contacts Size contacts Service	size no.	
No								ω
FR Not Listed PN: 8D115F05AB PN: 8D115F05AB A 27-09-2016 First Release ISS DATE Latest modification - by MOD M Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Inline plug 8D series SCALE General linear NPRDS / PROJECT NA Tolerances: 2: 859 1 This document is the property of SOUBIAUL SOUBIAUL	f the Products which does not comply with ssued by either of the Parties or by a third party	due the Spec						
ISS DATE Latest modification - by MOD N Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Inline plug 8D series SCALE General linear NPRDS / PROJECT NA Tolerances: 859 ± This document is the property of SOURIAU	FR Not Listed							N
SCALE General linear NPRDS / PROJECT NA Tolerances: 859 ± This document is the property of SOURIAU		ISS DATE Latest m						_
	General linear NPRDS / PROJECT Tolerances: 859	SCALE						_
FORMAT SOURIAU DRG N° SHEET	SOURIAU.COM SOURIAU it must not be reproduced or communicated without permission SOURIAU DRG N° SHEET	FORMAT						
A38D115F05AB-C2/2HGFEDCBA	8D115F05AB-C 2/2 B A	D A3	E	F	G		Н	