			0	₿ >		
4						
			LAYOUT SHOWN AS EXAM	MPLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension Dim Nominal	7				
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	ØS32.5 MaxZ31 MaxVV THREADM22x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer Contact Plating : Gold over copper Alloy 0.8μm minimum			Country FR	Jurisdiction & Control List Not Listed		
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D515F97PB			
-Temperature Range -65°C to +200°C		A 19-10-2016	First Release			
-Salt Spray : 48 hours 		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	
		TITLE	TITLE Aluminium Plug 8D series			
→ BASIC SERIES: 8D 5 - 15 F 9 → SHELL TYPE : Plug with RFI Shielding	97 P B	SCALE . NA	General linear Tolerances:	NPRDS / PROJECT 859		
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 15 CONTACT TYPE : PIN(500 Matings)			SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission			
PLATING : F = Nickel	CONTACT LA	YOUT : 15-97 FORMAT	SOURIAU D 8D515F97		SHEET	
			QDJJ2F3/	TD-L	-14	

	<u>т</u>	െ	וד	m	D	0
		Contact Layout				
4		$ \begin{array}{c} & & & & \\ & & & & \\ & & & \\ & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & $				
	Contact position ID Locati X-axis (mm) A +.065 (1.65) B +.178 (4.52) C +.230 (5.84) D +.178 (4.52) E +.065 (1.65) F 089 (2.26)	Y-axis (mm) position ID X-axis (mm) Y-axis (mm) + 234 (5.94) G - 207 (5.26) - 0.95 (2.41) + 178 (4.52) H - 234 (5.94) + 0.65 (4.65)				
	size no. cor	Iber of tacts Size contacts Service rating Contact location Supersedes 4 16 I C, G, L, M MS20052-97 8 20 I All others MS20052-97	-			
ယ						
	L					
	9					SOURIAU shall not be liable for ar due to a use of the Products w the Specifications issued by either o (professional recommenda
N						Count FR
					A 19-10	PN: 8D515
					ISS DA Designed By:	TE Latest modification - by Date:
					TITLE	
_					SCALE NA	General linear Tolerances:
					SOURI	
					FORMAT A3	SOURIAU 8D515F
	Н	G	F	E	D	C

