

Oct.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case that the application demands a high level of reliability, such as automotive,
 please contact a company representative for further information.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				
APPLICABLE STANDARD									
RATING	OPERATING TEMPERATURE RANGE	-30 °C TO 85 °C(NOTE 1)			STORAGE TEMPERATURE RANGE	-10 °C To + 60 °C			
	VOLTAGE				APPLICABLE CONNECTORS				
	CURRENT				OPERATING HUMIDITY RANGE	UL1007, AWG24			
SPECIFICATIONS									
ITEM		TEST METHOD			REQUIREMENTS			QT	AT
CONSTRUCTION									
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			X	X
MARKING		CONFIRMED VISUALLY.						X	X
REMARKS NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT					DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
					Y.NAGASHIMA	<i>Y. Inoue</i>	<i>Miyazaki</i>	<i>K. Katayama</i>	
Unless otherwise specified, refer to MIL-STD-1344.					'00.11.10	'00.11.10	'00.11.13	'00.11.14	
Note QT: Qualification Test AT: Assurance Test X:Applicable Test									
HRS HIROSE ELECTRIC CO., LTD.					SPECIFICATION SHEET			PART NO. DF1-*A1.33	
CODE NO.(OLD)		DRAWING NO.			PEART NO			1/1	
CL		ELC4-162341			CL541				

TO

