COUNT	NT DESCRIPTION OF REVIS			ONS BY CHKD		DATE COU		COUNT	T DESCRIPTION OF		REVISIONS	BY	CHKD	DAT	ΓE
APPLICABLE STANDARD															
OPERATING TEMPERATUR		RE RANGE	-35	°C TO +85		°C(NO	°C(NOTE1) T		STORAGE FEMPERATURE RANGE APPLICABLE		-10 °C TO +60				<u> </u>
RATING	VOLTAG	TAGE		250 V		/ AC			CONTACT		DF1B- * P-2.5DS			S(A)	
CURREN		ΙT	ΑV	AWG20-22		3/	3A				DF1BA- * EP-2.5RC				
			AV	AWG24-28		1A									
				AWG30		<u> </u>	0.5A								
SPECIFICATIONS ITEM TEST METHOD REQUIREMENTS QT AT															
	TEST MET				HOD			REQUIREMENTS Q					QT	ΑT	
	RUCTION	ly agreement	MOULAND DY MEA OUTDING MOTEUR							INO TO	DDAVA/INC				1
GENERAL E	VISUALLY AND BY MEASURING INSTRUMENT. CONFIRMED VISUALLY.							ACCORDING TO DRAWING.						×	
MARKING													×	×	
		ERISTICS							1 1 0 0 0 ΜΩ ΜΙΝ.						
VOLTAGE F		6 5 0 V AC FOR 1 min.						NO FLASHOVER OR BREAKDOWN.					×		
MECHANICAL CHARA															
	30 TIMES INSERTIONS AND EXTRACTIONS.							① NO DA		CRACK OR	LOOS	ENESS	×	_	
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, - m/s ² AT 2 h, FOR 3 DIRECTIONS.								AMAGE,	CRACK OR	LOOS	ENESS	×	-	
SHOCK		490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.							1					×	-
ENVIRO	NMENTAL					-									
RAPID CHA	TEMPERATURE -55→ 5~35 →+85→ 5~35 °C							1 -	ATION	RESISTANCI	E: 100	0 ΜΩ	×	_	
TEMPERATURE		TIME 30→10~15→ 30 →10~15 min UNDER 5 CYCLES.							MIN. ② NO DA OF PA		CRACK OR	LOOS	ENESS		
DAMP HEAT		EXPOSED AT 40 ± 2 °C, 90 ~ 95 %, 96 h.									RESISTANCI	E: 100	0 ΜΩ	×	
(STEADY STATE)									MIN. ② NO DAMAGE, CRACK OR LOOSENESS						
							<u></u>		OF PA	ARTS.	 			-	
1															
									1					!	
REMARKS					DRAWN			N DESI	GNED	CHECKED	APP	ROVED	RELE	ASED	
NOTE1: INCLUDE THE TEMPERATU				SING	BY CUR	KENI.	4	Inc	ue y. I	noue	T. Mizozeki	K.h	latazone		
Unless otherwise specified, refer to MIL-STD-1344. 100.9.14 100.9.14 100.9.14 100.9.18															
Note QT:Q	ualification Test	AT:Assu	ırance	Test	×:Applic	cable Test				0407	10				
HIROSE ELECTRIC CO., SPECIFICATION SHEET PART NO. DF1B- * S-2.5R															
CODE NO.(O	LD)	TI	DRAWII	NG NO	_ <u> </u>			P	ART NO.	L					1/
lcı (-					60017	7				CI 541				1'/

